

DATASHEET

Doc. rev. 0

CODICE: 6063-TE50

DESCRIZIONE: PANNELLO CONTROLLO LUCI AQUA

CODE: 6063-TE50

DESCRIPTION: AQUA LIGHT CONTROL PANEL







- L'immagine è puramente indicativa.
- Tecnovox si riserva il diritto di modificare il disegno o le caratteristiche per migliorare il prodotto senza preavviso.
- The picture is only indicative.
- Tecnovox reserve the right to change design or specifications to improve the product without notice.

FUNZIONI

- Tasto capacitivo per spegnere tutte le luci.
- Tasto capacitivo "OPEN DOOR" per pilotare l'incontro elettrico.
- Tasto capacitivo "DO NOT DISURB": quando il servizio è disabilitato Il tasto è illuminato bianco, quando è attivo è illuminato rosso.
- 4 tasti capacitivi per controllare 4 luci: il tasto può essere illuminato bianco (luce spenta), verde (luce accesa), gialla (luce in regolazione).
- Slide capacitiva " +" per regolare l'intensità della luce.

CARATTERISTICHE ELETTRICHE

- Tensione di alimentazione 12÷24 Vdc.
- Consumo energetico 2.4 W.
- Temperatura di esercizio 0÷40 °C.

CARATTERISTICHE MECCANICHE

- Montaggio a parete o ad incasso in scatola Gewiss GW48001.
- Ingombro: larghezza 114 mm, altezza 114 mm, profondità 9 mm.
- Peso: 150 g.

CONNESSIONI E CAVI

- Un connettore RJ45, 8 vie, 8 fili.
- Cavo: UTP CAT5

CARATTERISTICHE DEL PANNELLO

- Materiali: disponibile in policarbonato o vetro.
- Colori: disponibile nero o bianco o in qualunque altro colore RAL (personalizzato).

FUNCTIONS

- Capacitive button to turn off all lights.
- Capacitive button "OPEN DOOR" to drive electric strike.
- Capacitive button to active or disable "DO NOT DISTURB": when it's disabled the backlight is white, when it's active the backlight is red.
- 4 capacitive buttons to control 4 lights: white backlight (light off), green backlight (light on), yellow backlight (dimming).
- Capacitive slide "-+" to ajust the lights (dimming).

ELECTRICAL CHARACTERISTICS

- Power supply 12÷24 Vdc.
- Energy consumption 2.4 W.
- Operating temperature 0÷40 °C.

MECHANICAL CHARACTERISTICS

- Wall mounting or flush mounted in box Gewiss GW480001.
- Wall mounting: width 114 mm, height 114 mm, depth 9 mm.
- Peso: 150 g.

CONNECTIONS AND WIRES

- One RJ45 connector, 8 vias, 8 wire.
- Wire: UTP CAT5

PANEL FEATURES

- Materials: available in polycarbonate or glass.
- Colors: available black or white or in any RAL color (custom).

